

15oz./sq.yd. Vinyl Coated Polyester

**Email us for
a fabric sample.**

Applications

- Proective covers
- Gymnasium mats and pads
- Divider curtains
- Stationary tarpaulins
- Gymnasium floor coverings
- Many others

Typical Physical Properties

Property	Typical Test Results	Test Method
Total Weight (oz/yd ²)	15oz	ASTM D 3776
Tear (lb)	71 (w) X 45 (f)	ASTM D 751
Tensile (lb/inch)	228 (w) X 203 (f)	ASTM D 751
Adhesion (lb/inch)	15 (w) 22 (f)	ASTM D 751
Cold Crack (1/8" Mandrel)	-50° C	ASTM D 2136
Flame Retardancy	Pass (Class A) Pass Pass	ASTM E84 NFPA 701 ULCS 109
Stock Width	61"	
Stock Roll	68 metres/75 yards 120 lbs.	

Stock Colours

Maroon (A05-15110), White (A05-15120), Red (A05-15130),
Champion Blue (A05-15140), Sky Blue (A05-15150),
Navy Blue (A05-15160), Grey (A05-15180),
Black (A05-15190), Purple (A05-15200),
Orange (A05-15210), Beige (A05-15220),
Kelly Green (A05-15230), Yellow (A05-15240),
Forest Green (A05-15250)

This information is obtained by industry accepted test methods and represents typical data. It is for your general information only. There are no warranties expressed or implied. The information is furnished upon the condition that the people receiving it shall conduct their own tests to determine the suitability of our material for the particular application.

Features and Benefits

- Tear and abrasion resistant
- Flame retardant for the life of the fabric
- U.V. resistant for long life
- Rot and fungus resistant
- Dimensionally stable and shrink resistant
- Dielectrically and thermally weldable
- Resists internal and external mildewing
- Glossy leather grain finish

P.O. Box 277, Hamilton, Ontario L8N 3E8
Fax: (905)528-8128 e-mail: info@sopers.com

14-Aug-08