

Welding Amber PVC Strip

**Email us for
a fabric sample.**

The material has a UV inhibitor to resist cracking and yellowing from sunlight and therefore can be used both indoors and outdoors given its excellent overall weathering properties.

Property	
Width	8", 48" others upon request
Thickness	.080"
Specific gravity	1.24 (ASTM D792/DIN 51757)
Hardness shore A	78 (ASTM D2240/DIN 53505)
Tensile strength at break	2610 PSI (ASTM D638/DIN 53455)
Elongation at break	302% (ASTM D638/DIN 53455)
100% Modulus	1731 PSI
Tear resistance	324 lbs/inch (ASTM D1004/DIN 53515)
Cold temperature resistance	- 38°C (ASTM D746/DIN53372)
Surface resistivity	1880 megohms X 10 ⁶ (ASTM D257/DIN 53482)
Water absorption (4 days 23C)	0.04 weight % (SPI VD T12/DIN 53476)
Light transmittance	2.82% (Hunter)
Flammability	19 (ASTM D2863)
Ordering information	
B10-30080	8" X .080"
B10-30480	48" X .080"

The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained thereon. The information is based on laboratory work with small scale equipment and does not necessarily indicate end product performance. Full scale testing and product performance are the responsibility of the user.